

QNA-UC5G1T	
Interface	USB 3.0 to 5G/2.5G/1G/100M RJ-45 port
Data Transfer	5Gbps; 2.5Gbps; 1Gbps; 100Mbps
Cables	USB 3.0 Type-C to Type-A cable or USB Type-C to Type-C cable
Power Supply Unit	USB powered
System Requirements (Windows)	Windows 10, 8.1, 8, 7 requires a driver. <a href="#">Click here to download the driver.</a> *Required a USB 3.0 port on your computer
System Requirements (Mac)	Will be supported in the latest macOS Click <a href="#">here</a> to manually install the Aquantia® AQC11U driver *Required a USB 3.0 port on your computer
System Requirements (Linux)	Linux core 3.10, 3.12, 3.2, 4.2, 4.4 version. The driver for the Aquantia® AQC11U is required. *Required a USB 3.0 port on your computer
System Requirements (QNAP NAS)	QNAP NAS with QTS 4.3.6 (or above) and USB 3.0 port
Cable Length	100M CAT 6A: 40°
Operating Temperature & Relative Humidity	0 - 40 °C (32°F - 104°F); 5~95% (non-condensing)
Dimensions (H x W x D)	99.8 x 28 x 27.85 mm 3.93 x 1.10 x 1.10 inch
Weight	Net weight: 0.11 Kg, Gross weight: 0.21 Kg
LED Indicators	Power, LAN Link/Act, transfer speed
Package Contents	QNA-UC5G1T, 0.2M USB 3.0 Type-C to Type-A cable x 1, installation guide

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

\* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.